

Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

1 Identification

Product identifier

Trade name: ATE Testing Fluid 75:25

Article number: 03.9902-01xx.x / 70000x Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture hydraulic liquid

Details of the supplier of the safety data sheet Manufacturer/Supplier: Continental Aftermarket GmbH Guerickestr. 7 60488 Frankfurt a. M. Germany Tel: +49-69-76031

Fax: +49-69-761061

Information department:

Gefahrstoffmanagement Konzern, Zentrales Materiallabor ate.sicherheit@contiautomotive.com Emergency telephone number: +49-6132-84463

2 Hazard(s) identification

Classification of the substance or mixture



Health hazard

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms GHS08 Signal word Warning

Hazard-determining components of labeling:

2,2'-oxybisethanol

Hazard statements

May cause damage to the kidneys through prolonged or repeated exposure. Route of exposure: Oral.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray. Get medical advice/attention if you feel unwell.

Dispose of contents/container in accordance with local/regional/national/international regulations. Classification system:

NFPA ratings (scale 0 - 4)

 $0 \quad 0 \quad Health = 0$ Fire = 1 Reactivity = 0

HMIS-ratings (scale 0 - 4)

| HEALTH 0 | Health = 0 |
|--------------|------------------|
| FIRE 1 | Fire = 1 |
| REACTIVITY 0 | Reactivity = 0 |

(Contd. on page 2)

CA



Printing date 06/05/2015

Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

| Dangerous co | mponents: |
|--------------|-----------|
|--------------|-----------|

| 2 | | |
|-----------|---|-------|
| | Ethanol, 2-butoxy-, manufacture of, by-products from | <10% |
| | 🔶 Eye Dam. 1, H318 | |
| | 2,2'-oxybisethanol | <5% |
| | 🚸 STOT RE 2, H373; 🚸 Acute Tox. 4, H302 | |
| 5892-47-7 | 2,4,6-Tri-sec-butylphenol | <2.5% |
| | 🚯 Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315; Aquatic Acute 2, H401 | |
| | | |

4 First-aid measures

Description of first aid measures

General information: Remove contaminated clothes and shoes immediately.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:** Call a doctor immediately.

Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

For safety reasons unsuitable extinguishing agents: Water with full jet Special hazards arising from the substance or mixture

May be released in case of fire: CO, CO2, NOx

Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 3)

(Contd. of page 1)

CA



Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Printing date 06/05/2015

(Contd. of page 2) Do not allow to penetrate the ground/soil. **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the collected material according to regulations. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Storage at room temperature.

Information about storage in one common storage facility: Not required. Further information about storage conditions:

Store in dry conditions.

This product is hygroscopic.

Keep receptacle tightly sealed.

Storage class: 10 combustible liquids.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

If occupational exposure limits are exceeded, use breathing mask (filter type A). Wear selfcontained breathing apparatus in case of danger of oxygen displacement.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl caoutchouc (butyl rubber): minimum breakthrough times 180 min; minimum layer thickness: 0.7 mm

NBR (nitrile rubber): minimum breakthrough times 30 min; minimum layer thickness: 0.4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

(Contd. on page 4)

CA



*

Printing date 06/05/2015

Safety Data Sheet acc. to OSHA HCS

Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Limitation and supervision of exposure into the environment See section 6 and 7. No additional measures necessary.

| 9 Physical and chemical properties | | | |
|--|---|--|--|
| Information on basic physical and | Information on basic physical and chemical properties | | |
| General Information | | | |
| Appearance: | | | |
| Form: Color: | Fluid Yellow | | |
| Odor: | Characteristic | | |
| Odour threshold: | Not determined. | | |
| pH-value at 20 °C: | 7.5-9 | | |
| Change in condition | | | |
| Melting point/Melting range: | Undetermined. | | |
| Boiling point/Boiling range: | >265 °C | | |
| Flash point: | > 130 °C (DIN 51376) | | |
| Flammability (solid, gaseous): | Not applicable. | | |
| Ignition temperature: | > 200 °C (DIN 51794) | | |
| Decomposition temperature: | Not determined. | | |
| Auto igniting: | Product is not selfigniting. | | |
| Danger of explosion: | Product does not present an explosion hazard. | | |
| Explosion limits: | | | |
| Lower: | Not determined. | | |
| Upper: | Not determined. | | |
| Vapor pressure at 20 °C: | < 0.1 mbar | | |
| Density at 20 °C: | 1.05 g/cm³ (DIN 51757) | | |
| Relative density | Not determined. | | |
| Vapour density | Not determined. | | |
| Evaporation rate | Not determined. | | |
| Water: | Fully miscible. | | |
| Partition coefficient (n-octanol/water): Not determined. | | | |
| Viscosity: | | | |
| Dynamic: Kinematic at 20 °C: | Not determined. | | |
| | 40 mm²/s | | |
| Solvent content: | 10 5 0/ | | |
| Organic solvents: Other information | 13.5 % No further relevant information available. | | |
| | | | |

10 Stability and reactivity

Reactivity Chemical stability Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known. Conditions to avoid No further relevant information available. Incompatible materials: Strong oxidizing agents

(Contd. on page 5)

CA

(Contd. of page 3)



Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Printing date 06/05/2015

(Contd. of page 4) Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50 (Stäube und Nebel) 79 mg/l (rat)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known. Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Waste disponal according EC-regulations 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

⁻ CA -



Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. of page 5)

| Transport information | |
|--|-----------------------------------|
| UN-Number DOT, TDG, ADN, IMDG, IATA | Void |
| UN proper shipping name DOT, TDG, ADN, IMDG, IATA | Void |
| Transport hazard class(es) | |
| DOT, TDG, ADN, IMDG, IATA Class | Void |
| Packing group DOT, TDG, IMDG, IATA | Void |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user | Not applicable. |
| Transport in bulk according to Annex MARPOL73/78 and the IBC Code | t II of Not applicable. |
| UN "Model Regulation": | - |

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture Sara

| None of th | e ingredients is listed. | |
|------------------------|---|--|
| Section 3 ⁻ | 13 (Specific toxic chemical listings): | |
| None of th | e ingredients is listed. | |
| TSCA (To | xic Substances Control Act): | |
| 23783-42- | 8 2-(2-methoxyethoxy)ethanol | |
| 112-35- | 6 2-(2-(2-methoxyethoxy)ethoxy)ethanol | |
| 111-46- | 6 2,2'-oxybisethanol | |
| 112-27- | 6 2,2'-(ethylenedioxy)diethanol | |
| 143-22- | 6 2-[2-(2-butoxyethoxy)ethoxy]ethanol | |
| 112-60- | 7 3,6,9-trioxaundecane-1,11-diol | |
| 5892-47- | 7 2,4,6-Tri-sec-butylphenol | |
| 110-97- | 4 1,1'-iminodipropan-2-ol | |
| 15520-05- | 5 2,2 ⁻ -(Octylimino)bisethanol | |
| 67701-06- | 8 Fatty acids, C14-18 and C16-18-unsatd | |
| 68442-68- | 2 Benzenamine, N-phenyl-, styrenated | |
| 4314-14- | 1 Fat Yellow 3G | |
| 8042-47- | 5 White mineral oil (petroleum) | |
| 68439-46- | 3 Alcohol ethoxylate (C9-C11, 6 EO) | |
| 68188-18- | 1 Paraffin oils, sulfochlorinated, saponified | |



Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Printing date 06/05/2015

| Proposition | 65 | (Contd. of page |
|---------------|--|-----------------|
| - | nown to cause cancer: | |
| None of the i | ngredients is listed. | |
| Chemicals k | nown to cause reproductive toxicity for females: | |
| None of the i | ngredients is listed. | |
| Chemicals k | nown to cause reproductive toxicity for males: | |
| | ngredients is listed. | |
| Chemicals k | nown to cause developmental toxicity: | |
| | ngredients is listed. | |
| Cancerogen | ity categories | |
| | nmental Protection Agency) | |
| None of the i | ngredients is listed. | |
| TLV (Thresh | old Limit Value established by ACGIH) | |
| None of the i | ngredients is listed. | |
| NIOSH-Ca (I | National Institute for Occupational Safety and Health) | |
| None of the i | ngredients is listed. | |
| Canadian su | Ibstance listings: | |
| Canadian De | omestic Substances List (DSL) | |
| 30989-05-0 | MTG-100-Borate | |
| 23783-42-8 | 2-(2-methoxyethoxy)ethanol | |
| | 2-(2-(2-methoxyethoxy)ethoxy)ethanol | |
| | 2,2'-oxybisethanol | |
| | 2,2'-(ethylenedioxy)diethanol | |
| | 2-[2-(2-butoxyethoxy)ethoxy]ethanol | |
| | 3,6,9-trioxaundecane-1,11-diol | |
| | 2,4,6-Tri-sec-butylphenol | |
| | 1,1'-iminodipropan-2-ol | |
| | Fatty acids, C14-18 and C16-18-unsatd | |
| | Benzenamine, N-phenyl-, styrenated | |
| | Fat Yellow 3G | |
| | White mineral oil (petroleum) | |
| | Alcohol ethoxylate (C9-C11, 6 EO) | |
| 68188-18-1 | Paraffin oils, sulfochlorinated, saponified | |
| Canadian In | gredient Disclosure list (limit 0.1%) | |
| None of the i | ngredients is listed. | |
| Canadian In | gredient Disclosure list (limit 1%) | |
| 112-27-6 2,2 | 2'-(ethylenedioxy)diethanol | |
| 143-22-6 2-6 | 2-(2-butoxyethoxy)ethoxy]ethanol | |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Recommended restriction of use For industrial purposes only. Date of preparation / last revision 06/05/2015 / 3 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)

⁻ CA



Version 4

Reviewed on 05/30/2015

Trade name: ATE Testing Fluid 75:25

Printing date 06/05/2015

| | (Contd. of page 7) |
|---|--------------------|
| DOT: US Department of Transportation | |
| IATA: International Air Transport Association | |
| ACGIH: American Conference of Governmental Industrial Hygienists | |
| EINECS: European Inventory of Existing Commercial Chemical Substance | es |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Soc | cietv) |
| NFPA: National Fire Protection Association (USA) | |
| HMIS: Hazardous Materials Identification System (USA) | |
| LC50: Lethal concentration, 50 percent | |
| LD50: Lethal dose, 50 percent | |
| Acute Tox. 4: Acute toxicity, Hazard Category 4 | |
| Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 | |
| Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 | |
| STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard C | Category 2 |
| Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, C | |
| Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Haza | |
| Sources | |
| | |
| * Data compared to the previous version altered. | |
| | CA |
